



# SEALTITE B


## PRODUCT DESCRIPTION

- Sealtite B is composed of an open micro-cell polyurethane foam impregnated with a flame retardant, hydrophobic, acrylic resin
- Sealtite B is supplied precompressed
- Sealtite B is supplied in both rolls and sticks
- Sealtite B is designed to function as a secondary seal in vertical applications, such as window and flashing applications



## COLORS

Sealtite B is available in Black



Black

## LIMITATIONS AND INSTALLATION CONSIDERATIONS

- Joints must be sized by measuring every 5 – 7 feet to ensure gap opening is uniform and depth is sufficient for the supplied material
- Will not adhere properly to surfaces contaminated by oil, grease, or dust
- Store material in a dry, enclosed area, off the ground, and out of direct sunlight. Do not install when raining or snowing

## NOT INTENDED FOR

- Joints submerged in water
- Joints in contact with harsh chemicals
- Horizontal joints
- Primary joint applications
- Cross joints in copings and projecting stonework

## WARRANTY

Schul Products are warranted to be free of defects in materials, but no warranty is made as to appearance or color. No other warranty, expressed or implied, is made with respect to Schul Products, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE. The sole and exclusive remedy under this warranty shall be to replace or refund the purchase price of the quantity of Schul Products proven to be defective, and there is no liability whatsoever for other loss or damage.



INTERNATIONAL QUALITY REGISTRARS CORP.  
QUALITY SYSTEM REGISTRATION; ISO 9001 CERTIFIED

SCHUL INTERNATIONAL COMPANY  
TELEPHONE: (800) 848-1120 ● FAX: (800) 998-9105 ● WEB ADDRESS: [www.schul.com](http://www.schul.com)  
34 EXECUTIVE DRIVE, HUDSON, NH 03051